

# PRODUCT OVERVIEW 11/2021



# CONTENTS

## Colour Systems

<b>A3 Multifunctional Systems</b>	<b>page 3</b>
<b>A4 Multifunctional Systems</b>	<b>page 5</b>
<b>A4 Print Systems</b>	<b>page 8</b>

## b/w Systems

<b>A3 Multifunctional Systems</b>	<b>page 9</b>
<b>A4 Multifunctional Systems</b>	<b>page 11</b>
<b>A3 Print System</b>	<b>page 15</b>
<b>A4 Print Systems</b>	<b>page 16</b>

# A3 MULTIFUNCTIONAL SYSTEMS



		P-C2480i MFP	2508ci	3508ci	4008ci
<b>Copy</b>	Copy speed	24 A4 / 12 A3 pages/min in colour and b/w	25 A4 / 12 A3 pages/min in colour and b/w	35 A4 / 17 A3 pages/min in colour and b/w	40 A4 / 20 A3 pages/min in colour and b/w
	Copy resolution	600 x 600 dpi	600 x 600 dpi	600 x 600 dpi	600 x 600 dpi
	Greyscales	256	256	256	256
	Standard paper feed	600 (500 + 100 sheets)	1,150 (2 x 500 + 150 sheets)	1,150 (2 x 500 + 150 sheets)	1,150 (2 x 500 + 150 sheets)
	Optional paper feed	1 or 2 x 500 sheets	2 x 500, 2 x 1,500, 3,000 sheets, different combinations possible	2 x 500, 2 x 1,500, 3,000 sheets, different combinations possible	2 x 500, 2 x 1,500, 3,000 sheets, different combinations possible
	Paper capacity, max	1,600 sheets	7,150 sheets	7,150 sheets	7,150 sheets
	Paper format	A6R-A3	A6R-SRA3/A3+	A6R-SRA3/A3+	A6R-SRA3/A3+
	Original feeder	Standard	Option: DP-7140, DP-7150, DP-7160 or DP-7170	Option: DP-7140, DP-7150, DP-7160 or DP-7170	Option: DP-7150, DP-7160 or DP-7170
	Duplex	Standard	Standard	Standard	Standard
	System memory	1.5 GB (max 3 GB)	4 GB RAM, 32 GB SSD/320 GB or 1 TB HDD	4 GB RAM, 32 GB SSD/320 GB or 1 TB HDD	4 GB RAM, 64 GB SSD/320 GB or 1 TB HDD
Zoom	25%-400%	25%-400%	25%-400%	25%-400%	
Cabinet	Option: no. 62	Option: no. 81	Option: no. 81	Option: no. 81	
<b>Print</b>	Type	Integrated within the system	Integrated within the system	Integrated within the system	Integrated within the system
	Interfaces	USB 2.0, 10/100/1000BaseTX, USB host (2), NFC, Wi-Fi	USB 3.0, USB 2.0, 10/100/1000BaseTX, USB host, NFC	USB 3.0, USB 2.0, 10/100/1000BaseTX, USB host, NFC	USB 3.0, USB 2.0, 10/100/1000BaseTX, USB host, NFC
	Operating systems	Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016/2019, Novell NetWare, Linux, Mac ex OS 10.8	Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016/2019, Novell NetWare, Linux, Mac ex OS 10.9	Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016/2019, Novell NetWare, Linux, Mac ex OS 10.9	Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016/2019, Novell NetWare, Linux, Mac ex OS 10.9
Emulations	PCL6 (5c, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIC, XPS	PCL6 (5c, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIC, PDF 2.0, XPS	PCL6 (5c, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIC, PDF 2.0, XPS	PCL6 (5c, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIC, PDF 2.0, XPS	
<b>Network</b>	Interfaces	10/100/1000BaseTX	10/100/1000BaseTX	10/100/1000BaseTX	10/100/1000BaseTX
	Network protocols	TCP/IP, Net BEUI	TCP/IP, Net BEUI	TCP/IP, Net BEUI	TCP/IP, Net BEUI
	Operating systems	Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016/2019	Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016/2019	Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016/2019	Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016/2019
<b>Scan</b>	Scan type	CIS colour and b/w	CCD colour and b/w	CCD colour and b/w	CCD colour and b/w
	Scan resolution	200, 300, 400, 600 dpi	200, 300, 400, 600 dpi	200, 300, 400, 600 dpi	200, 300, 400, 600 dpi
	Interfaces	10/100/1000BaseTX, USB 2.0	10/100/1000BaseTX	10/100/1000BaseTX	10/100/1000BaseTX
	Network protocols	TCP/IP	TCP/IP	TCP/IP	TCP/IP
<b>Fax</b>	Originals	max A3	max A3	max A3	max A3
	Modem speed	33.6 kbps	33.6 kbps	33.6 kbps	33.6 kbps
	Compression method	JBIG, MMR, MR, MH	JBIG, MMR, MR, MH	JBIG, MMR, MR, MH	JBIG, MMR, MR, MH
	One-touch dial/abbr. dial	100/200	1,000/2,000	1,000/2,000	1,000/2,000

# A3 MULTIFUNCTIONAL SYSTEMS



		5008ci	6008ci	7008ci	8307ci
<b>Copy</b>	Copy speed	50 A4 / 25 A3 pages/min in colour and b/w	60 A4 / 30 A3 pages/min in colour and b/w	70 A4 / 35 A3 pages/min in colour and b/w	70/83 A4 / 35/41 A3 pages/min in colour and b/w
	Copy resolution	600 x 600 dpi	600 x 600 dpi	600 x 600 dpi	600 x 600 dpi
	Greyscales	256	256	256	256
	Standard paper feed	1,150 (2 x 500 + 150 sheets)	1,150 (2 x 500 + 150 sheets)	1,150 (2 x 500 + 150 sheets)	4,150 (2 x 500 + 2 x 1,500 + 150 sheets)
	Optional paper feed	2 x 500, 2 x 1,500, 3,000 sheets, different combinations possible	2 x 500, 2 x 1,500, 3,000 sheets, different combinations possible	2 x 500, 2 x 1,500, 3,000 sheets, different combinations possible	2 x 500, 2 x 1,500, 3,000 sheets, different combinations possible
	Paper capacity, max	7,150 sheets	7,650 sheets	7,650 sheets	7,650 sheets
	Paper format	A6R-SRA3/A3+	A6R-SRA3/A3+	A6R-SRA3/A3+	A6R-A3+
	Original feeder	Option: DP-7150, DP-7160 or DP-7170	Option: DP-7150, DP-7160 or DP-7170	Option: DP-7150, DP-7160 or DP-7170	Standard (dual scan with multi-feed detection)
	Duplex	Standard	Standard	Standard	Standard
	System memory	4 GB RAM, 64 GB SSD/320 GB HDD or 1 TB HDD	4 GB RAM, 64 GB SSD/320 GB HDD or 1 TB HDD	4 GB RAM, 64 GB SSD/320 GB HDD or 1 TB HDD	4.5 GB RAM, 8 GB SSD/320 GB HDD
Zoom	25%-400%	25%-400%	25%-400%	25%-400%	
Cabinet	Option: no. 81	Option: no. 81	Option: no. 81	--	
<b>Print</b>	Type	Integrated within the system	Integrated within the system	Integrated within the system	Integrated within the system
	Interfaces	USB 3.0, USB 2.0, 10/100/1000BaseTX, USB host, NFC	USB 3.0, USB 2.0, 10/100/1000BaseTX, USB host, NFC	USB 3.0, USB 2.0, 10/100/1000BaseTX, USB host, NFC	USB 2.0, 10/100/1000BaseTX, USB host, NFC
	Operating systems	Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016/2019, Novell NetWare, Linux, Mac ex OS 10.9	Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016/2019, Novell NetWare, Linux, Mac ex OS 10.9	Windows 7/8/8.1/10, Server 2008 R2/2012 R2/2016/2019, Novell NetWare, Linux, Mac ex OS 10.9	Windows 7/8/8.1/10, Server 2008 R2/2012 R2/2016/2019, Novell NetWare, Linux, Mac ab OS 10.9
Emulations	PCL6 (5c, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIC, PDF 2.0, XPS	PCL6 (5c, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIC, PDF 2.0, XPS	PCL6 (5c, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIC, PDF 2.0, XPS	PCL6 (5c, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIC, XPS	
<b>Network</b>	Interfaces	10/100/1000BaseTX	10/100/1000BaseTX	10/100/1000BaseTX	10/100/1000BaseTX
	Network protocols	TCP/IP, Net BEUI	TCP/IP, Net BEUI	TCP/IP, Net BEUI	TCP/IP, Net BEUI
	Operating systems	Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016/2019	Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016/2019	Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016/2019	Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016/2019
<b>Scan</b>	Scan type	CCD colour and b/w	CCD colour and b/w	CCD colour and b/w	CCD colour and b/w
	Scan resolution	200, 300, 400, 600 dpi	200, 300, 400, 600 dpi	200, 300, 400, 600 dpi	200, 300, 400, 600 dpi
	Interfaces	10/100/1000BaseTX	10/100/1000BaseTX	10/100/1000BaseTX	10/100/1000BaseTX
	Network protocols	TCP/IP	TCP/IP	TCP/IP	TCP/IP
<b>Fax</b>	Originals	max A3	max A3	max A3	max A3
	Modem speed	33.6 kbps	33.6 kbps	33.6 kbps	33.6 kbps
	Compression method	JBIG, MMR, MR, MH	JBIG, MMR, MR, MH	JBIG, MMR, MR, MH	JBIG, MMR, MR, MH
	One-touch dial/abbr. dial	1,000/2,000	1,000/2,000	1,000/2,000	1,000/2,000

# A4 MULTIFUNCTIONAL SYSTEMS



		302ci	352ci	402ci	502ci
<b>Copy</b>	Copy speed	30 A4 pages/min. in colour and b/w	35 A4 pages/min. in colour and b/w	40 A4 pages/min. in colour and b/w	50 A4 pages/min. in colour and b/w
	Copy resolution	600 x 600 dpi	600 x 600 dpi	600 x 600 dpi	600 x 600 dpi
	Greyscales	256	256	256	256
	Standard paper feed	600 (1 x 500 + 100 sheets)	600 (1 x 500 + 100 sheets)	600 (1 x 500 + 100 sheets)	600 (1 x 500 + 100 sheets)
	Optional paper feed	1 x 500 + 2 x 500 or 1 x 2,000 sheets	1 x 500 + 2 x 500 or 1 x 2,000 sheets	1 x 500 + 2 x 500 or 1 x 2,000 sheets	1 x 500 + 2 x 500 or 1 x 2,000 sheets
	Paper capacity, max	3,100 sheets	3,100 sheets	3,100 sheets	3,100 sheets
	Paper format	A6R-A4	A6R-A4	A6R-A4	A6R-A4
	Original feeder	Standard	Option: DP-5100, DP-5120, DP-5130	Option: DP-5100, DP-5120, DP-5130	Option: DP-5100, DP-5120, DP-5130
	Duplex	Standard	Standard	Standard	Standard
System memory	1.536 MB RAM (max. 3.072 MB RAM)	4 GB RAM, 16 GB SSD/320 GB HDD	4 GB RAM, 8 GB SSD, 320 GB HDD	4 GB RAM, 8 GB SSD, 320 GB HDD	
Zoom	25%-400%	25%-400%	25%-400%	25%-400%	
Cabinet	Option: high Nr. 74, low Nr. 75	Option: high Nr. 74, low Nr. 75	Option: high Nr. 74, low Nr. 75	Option: high Nr. 74, low Nr. 75	
<b>Print</b>	Type	Integrated within the system	Integrated within the system	Integrated within the system	Integrated within the system
	Interfaces	USB 2.0 (opt.), 10/100/1000BaseTX, USB host (2)	USB 2.0 (opt.), 10/100/1000BaseTX, USB-Host (3), NFC	USB 2.0 (opt.), 10/100/1000BaseTX, USB-Host (3), NFC	USB 2.0 (opt.), 10/100/1000BaseTX, USB-Host (3), NFC
	Operating systems	Windows 7/8.1/10, Server 2008 R2/2012 R2/2016/2019, Novell NetWare, Linux, Mac ex OS 10.9	Windows 7/8.1/10, Server 2003/2008 R2/2012 R2/2016/2019, Novell NetWare, Linux, Mac ex OS 10.9	Windows 7/8.1/10, Server 2003/2008 R2/2012 R2/2016/2019, Novell NetWare, Linux, Mac ex OS 10.9	Windows 7/8.1/10, Server 2003/2008 R2/2012 R2/2016/2019, Novell NetWare, Linux, Mac ex OS 10.9
Emulations	PCL6 (5c, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIc, PDF 1.7, XPS, OpenXPS	PCL6 (5c, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIc, PDF 1.7, XPS, OpenXPS	PCL6 (5c, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIc, PDF 1.7, XPS, OpenXPS	PCL6 (5c, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIc, PDF 1.7, XPS, OpenXPS	
<b>Network</b>	Interfaces	10/100/1000BaseTX	10/100/1000BaseTX	10/100/1000BaseTX	10/100/1000BaseTX
	Network protocols	TCP/IP, Net BEUI	TCP/IP, Net BEUI	TCP/IP, Net BEUI	TCP/IP, Net BEUI
	Operating systems	Windows 7/8.1/10, Server 2008/2008R2/2012/2012R2/2016/2019	Windows 7/8.1/10, Server 2008/2008R2/2012/2012 R2/2016/2019	Windows 7/8.1/10, Server 2008/2008R2/2012/2012 R2/2016/2019	Windows 7/8.1/10, Server 2008/2008R2/2012/2012 R2/2016/2019
<b>Scan</b>	Scan type	CCD colour and b/w	CCD colour and b/w	CCD colour and b/w	CCD colour and b/w
	Scan resolution	200, 300, 400, 600 dpi	200, 300, 400, 600 dpi	200, 300, 400, 600 dpi	200, 300, 400, 600 dpi
	Interfaces	10/100/1000BaseTX, USB 2.0	10/100/1000BaseTX, USB 2.0	10/100/1000BaseTX, USB 2.0	10/100/1000BaseTX, USB 2.0
	Network protocols	TCP/IP	TCP/IP	TCP/IP	TCP/IP
<b>Fax</b>	Originals	max A4	max A4	max A4	max A4
	Modem speed	33,6 kbps	33,6 kbps	33,6 kbps	33,6 kbps
	Compression method	JBIG, MMR, MR, MH	JBIG, MMR, MR, MH	JBIG, MMR, MR, MH	JBIG, MMR, MR, MH
	One-touch dial/abbr. dial	100/200	1,000/2,000	1,000/2,000	1,000/2,000

# A4 MULTIFUNCTIONAL SYSTEMS



**P-C2655w MFP**



**357ci**

<b>Copy</b>	Copy speed	26 A4 pages/min in colour and b/w	35 A4 pages/min in colour and b/w
	Copy resolution	600 x 600 dpi	600 x 600 dpi
<b>Print</b>	Greyscales	256	256
	Standard paper feed	300 (1 x 250 + 50 sheets)	350 (1 x 250 + 100 sheets)
	Optional paper feed	1 x 250 sheets	3 x 500 sheets
	Paper capacity, max	550 sheets	1,850 sheets
	Paper format	A6R-A4	A6R-A4
	Original feeder	Standard (Duplex Scan)	Standard (Duplex Scan)
	Duplex	Standard	Standard
	System memory	512 MB RAM (max 1,536 MB)	1,024 MB RAM (max 3,072 MB RAM)
	Zoom	25%–400%	25%–400%
	Cabinet	Option: no. 77	Option: high no. 72, low no. 73
<b>Network</b>	Type	Integrated within the system	Integrated within the system
	Interfaces	USB 2.0, 10/100/1000BaseTX, USB host, SD slot, Wi-Fi	USB 2.0, 10/100/1000BaseTX, USB host (2)
	Operating systems	Windows XP, Vista, Windows 7/8/8.1/10, Server 2003/2008 R2/2012 R2/2016/2019, Linux, Mac ex OS 10.6	Windows 7/8/8.1/10, Server 2008 R2/2012 R2/2016/2019, Novell NetWare, Linux, Mac ex OS 10.9
<b>Scan</b>	Emulations	PCL6 (5c, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIc, PDF 1.7, XPS, Open XPS	PCL6 (5c, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIc, PDF 1.7, XPS
	Interfaces	10/100/1000BaseTX	10/100/1000BaseTX
<b>Fax</b>	Network protocols	TCP/IP, Net BEUI	TCP/IP, Net BEUI
	Operating systems	Windows XP, Vista, Windows 7/8/8.1/10, Server 2003/2008 R2/2012 R2	Windows 7/8/8.1/10, Server 2008/2008R2/2012/2012R2/2016/2019
	Scan type	CIS colour and b/w	CCD colour and b/w
<b>Network</b>	Scan resolution	200, 300, 400, 600 dpi	200, 300, 400, 600 dpi
	Interfaces	10/100/1000BaseTX, USB 2.0	10/100/1000BaseTX, USB 2.0
	Network protocols	TCP/IP	TCP/IP
<b>Fax</b>	Originals	max A4	max A4
	Modem speed	33.6 kbps	33.6 kbps
	Compression method	JBIG, MMR, MR, MH	JBIG, MMR, MR, MH
	One-touch dial/abbr. dial	100/200	100/200

# A4 MULTIFUNCTIONAL SYSTEMS



**P-C3062i MFP**



**P-C3562i MFP**

		<b>P-C3062i MFP</b>	<b>P-C3066i MFP</b>	<b>P-C3562i MFP</b>	<b>P-C3566i MFP</b>
<b>Copy</b>	Copy speed	30 A4 pages/min in colour and b/w	30 A4 pages/min in colour and b/w	35 A4 pages/min in colour and b/w	35 A4 pages/min in colour and b/w
	Copy resolution	600 x 600 dpi	600 x 600 dpi	600 x 600 dpi	600 x 600 dpi
	Greyscales	256	256	256	256
	Standard paper feed	350 (1 x 250 + 100 sheets)	350 (1 x 250 + 100 sheets)	350 (1 x 250 + 100 sheets)	350 (1 x 250 + 100 sheets)
	Optional paper feed	3 x 500 sheets	3 x 500 sheets	3 x 500 sheets	3 x 500 sheets
	Paper capacity, max	1,850 sheets	1,850 sheets	1,850 sheets	1,850 sheets
	Paper format	A6R-A4	A6R-A4	A6R-A4	A6R-A4
	Original feeder	Standard	Standard	Standard (Duplex Scan)	Standard (Duplex Scan)
	Duplex	Standard	Standard	Standard	Standard
	System memory	1,024 MB RAM (max 3,072 MB RAM)	1,024 MB RAM (max 3,072 MB RAM)	1,024 MB RAM (max 3,072 MB RAM)	1,024 MB RAM (max 3,072 MB RAM)
Zoom	25%–400%	25%–400%	25%–400%	25%–400%	
Cabinet	Option: high no. 72, low no. 73	Option: high no. 72, low no. 73	Option: high no. 72, low no. 73	Option: high no. 72, low no. 73	
<b>Print</b>	Type	Integrated within the system	Integrated within the system	Integrated within the system	Integrated within the system
	Interfaces	USB 2.0, 10/100/1000BaseTX, USB host (2)	USB 2.0, 10/100/1000BaseTX, USB host (2)	USB 2.0, 10/100/1000BaseTX, USB host (2)	USB 2.0, 10/100/1000BaseTX, USB host (2)
	Operating systems	Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016/2019, Novell NetWare, Linux, Mac ex OS 10.5	Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016/2019, Novell NetWare, Linux, Mac ex OS 10.5	Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016/2019, Novell NetWare, Linux, Mac ex OS 10.5	Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016/2019, Novell NetWare, Linux, Mac ex OS 10.5
Emulations	PCL6 (5c, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIc, PDF 1.7, XPS	PCL6 (5c, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIc, PDF 1.7, XPS	PCL6 (5c, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIc, PDF 1.7, XPS	PCL6 (5c, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIc, PDF 1.7, XPS	
<b>Network</b>	Interfaces	10/100/1000BaseTX	10/100/1000BaseTX	10/100/1000BaseTX	10/100/1000BaseTX
	Network protocols	TCP/IP, Net BEUI	TCP/IP, Net BEUI	TCP/IP, Net BEUI	TCP/IP, Net BEUI
	Operating systems	Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016/2019	Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016/2019	Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016/2019	Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016/2019
<b>Scan</b>	Scan type	CCD colour and b/w	CCD colour and b/w	CCD colour and b/w	CCD colour and b/w
	Scan resolution	200, 300, 400, 600 dpi	200, 300, 400, 600 dpi	200, 300, 400, 600 dpi	200, 300, 400, 600 dpi
	Interfaces	10/100/1000BaseTX, USB 2.0	10/100/1000BaseTX, USB 2.0	10/100/1000BaseTX, USB 2.0	10/100/1000BaseTX, USB 2.0
	Network protocols	TCP/IP	TCP/IP	TCP/IP	TCP/IP
<b>Fax</b>	Originals	--	max A4	--	max A4
	Modem speed	--	33.6 kbps	--	33.6 kbps
	Compression method	--	JBIG, MMR, MR, MH	--	JBIG, MMR, MR, MH
	One-touch dial/abbr. dial	--	100/200	--	100/200

# A4 PRINT SYSTEMS



## P-C2650DW

<b>Print format</b>	A6R-A4
<b>Print speed</b>	26 A4 pages/min in colour and b/w
<b>Print resolution</b>	600 x 600 dpi, 9,600 x 600 dpi level, 1,200 x 1,200 dpi (reduced speed)
<b>Standard paper feed</b>	300 (1 x 250 + 50 sheets)
<b>Optional paper feed</b>	1 x 250 sheets
<b>Duplex</b>	Standard
<b>Processor</b>	Cortex-A9 / 800 MHz
<b>Print memory</b>	512 MB (max 512 MB)
<b>Interfaces</b>	USB 2.0, 10/100/1000BaseTX, USB host, SD slot, Wi-Fi
<b>Network card optional</b>	--
<b>Emulations</b>	PCL6 (5c, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIc, PDF 1.7, XPS, Open XPS



## P-C3062DN

<b>Print format</b>	A6R-A4
<b>Print speed</b>	30 A4 pages/min in colour and b/w
<b>Print resolution</b>	600 x 600 dpi, max 1,200 x 1,200 dpi (reduced speed)
<b>Standard paper feed</b>	600 (1 x 500 + 100 sheets)
<b>Optional paper feed</b>	3 x 500 sheets
<b>Duplex</b>	Standard
<b>Processor</b>	ARM Cortex-A9 dual core/1.2 GHz
<b>Print memory</b>	1,024 MB (max 1,024 MB)
<b>Interfaces</b>	USB 2.0, 10/100/1000BaseTX, USB host (2)
<b>Network card optional</b>	IB-50 Gigabit Ethernet, IB-36/IB-51 WLAN card
<b>Emulations</b>	PCL6 (5c, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIc, PDF 1.7, XPS



## P-C3562DN

<b>Print format</b>	A6R-A4
<b>Print speed</b>	35 A4 pages/min in colour and b/w
<b>Print resolution</b>	600 x 600 dpi, max 1,200 x 1,200 dpi (reduced speed)
<b>Standard paper feed</b>	600 (1 x 500 + 100 sheets)
<b>Optional paper feed</b>	3 x 500 sheets
<b>Duplex</b>	Standard
<b>Processor</b>	ARM Cortex-A9 dual core/1.2 GHz
<b>Print memory</b>	1,024 MB (max 3,072 MB)
<b>Interfaces</b>	USB 2.0, 10/100/1000BaseTX, USB host (2)
<b>Network card optional</b>	IB-50 Gigabit Ethernet, IB-36/IB-51 WLAN card
<b>Emulations</b>	PCL6 (5c, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIc, PDF 1.7, XPS

## P-C4072DN

<b>Print format</b>	A6R-A4
<b>Print speed</b>	40 A4 pages/min in colour and b/w
<b>Print resolution</b>	600 x 600 dpi, max 1,200 x 1,200 dpi (reduced speed)
<b>Standard paper feed</b>	600 (1 x 500 + 100 sheets)
<b>Optional paper feed</b>	3 x 500 sheets
<b>Duplex</b>	Standard
<b>Processor</b>	ARM Cortex-A9 dual core/1.2 GHz
<b>Print memory</b>	1,024 MB (max 3,072 MB)
<b>Interfaces</b>	USB 2.0, 10/100/1000BaseTX, USB host (2)
<b>Network card optional</b>	IB-50 Gigabit Ethernet, IB-36/IB-51 WLAN card
<b>Emulations</b>	PCL6 (5c, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIc, PDF 1.7, XPS



# A3 MULTIFUNCTIONAL SYSTEMS



		P-2540i MFP	3262i	4062i
<b>Copy</b>	Copy speed	25 A4 / 12 A3 pages/min	32 A4 / 17 A3 pages/min	40 A4 / 21 A3 pages/min
	Copy resolution	600 x 600 dpi	600 x 600 dpi	600 x 600 dpi
	Greyscales	256	256	256
	Standard paper feed	600 (1 x 500 + 100 sheets)	1,100 (2 x 500 + 100 sheets)	1,100 (2 x 500 + 100 sheets)
	Optional paper feed	1 or 2 x 500 sheets	2 x 500 sheets or 2 x 1,500 sheets	2 x 500 sheets or 2 x 1,500 sheets
	Paper capacity, max	1,600 sheets	4,100 sheets	4,100 sheets
	Paper format	A6R-A3	A6R-A3	A6R-A3
	Original feeder	Standard	Option: DP-7100, DP-7110 or DP-7120	Option: DP-7100, DP-7110 or DP-7120
	Duplex	Standard	Standard	Standard
	System memory	1 GB (max 3 GB)	2 GB RAM, 32 GB SSD / 320 GB HDD	2 GB RAM, 8 GB SSD / 320 GB HDD
Zoom	25%-400%	25%-400%	25%-400%	
Cabinet	Option: no. 22	Option: no. 70	Option: no. 70	
<b>Print</b>	Type	Integrated within the system	Integrated within the system	Integrated within the system
	Interfaces	USB 2.0, 10/100/1000BaseTX, USB host (2), NFC, Wi-Fi	USB 2.0, 10/100/1000BaseTX, USB host	USB 2.0, 10/100/1000BaseTX, USB host
	Operating systems	Windows 7/8.1/10, Server 2008 R2/2012 R2/2016/2019, Novell NetWare, Linux, Mac ex OS 10.5	Windows 7/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016/2019, Novell NetWare, Linux, Mac ex OS 10.8	Windows 7/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016/2019, Novell NetWare, Linux, Mac ex OS 10.8
Emulations	PCL6 (5c, XL), KPDL 3 (PostScript 3 compatible), XPS, PRESCRIBE IIe, PDF 1.7	PCL6 (5e, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIe, XPS	PCL6 (5e, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIe, XPS	
<b>Network</b>	Interfaces	10/100/1000BaseTX	10/100/1000BaseTX	10/100/1000BaseTX
	Network protocols	TCP/IP, Net BEUI	TCP/IP, Net BEUI	TCP/IP, Net BEUI
	Operating systems	Windows 7/8.1/10, Server 2008 R2/2012 R2/2016/2019	Windows 7/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016/2019	Windows 7/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016/2019
<b>Scan</b>	Scan type	CIS colour and b/w	CCD colour and b/w	CCD colour and b/w
	Scan resolution	200, 300, 400, 600 dpi	200, 300, 400, 600 dpi	200, 300, 400, 600 dpi
	Interfaces	10/100/1000BaseTX, USB 2.0	10/100/1000BaseTX	10/100/1000BaseTX
	Network protocols	TCP/IP	TCP/IP	TCP/IP
<b>Fax</b>	Originals	max A3	max A3	max A3
	Modem speed	33.6 kbps	33.6 kbps	33.6 kbps
	Compression method	JBIG, MMR, MR, MH	JBIG, MMR, MR, MH	JBIG, MMR, MR, MH
	One-touch dial/abbr. dial	100/200	1,000/2,000	1,000/2,000

# A3 MULTIFUNCTIONAL SYSTEMS



		5058i	6058i	7058i	8057i
<b>Copy</b>	Copy speed	50 A4 / 25 A3 pages/min	60 A4 / 30 A3 pages/min	70 A4 / 35 A3 pages/min	80 A4 / 40 A3 pages/min
	Copy resolution	600 x 600 dpi	600 x 600 dpi	600 x 600 dpi	600 x 600 dpi
	Greyscales	256	256	256	256
	Standard paper feed	1,150 (2 x 500 + 150 sheets)	1,150 (2 x 500 + 150 sheets)	1,150 (2 x 500 + 150 sheets)	4,150 (2 x 500 + 2 x 1,500 + 150 sheets)
	Optional paper feed	2 x 500, 2 x 1,500, 3,000 sheets, different combinations possible	2 x 500, 2 x 1,500, 3,000 sheets, different combinations possible	2 x 500, 2 x 1,500, 3,000 sheets, different combinations possible	2 x 500, 2 x 1,500, 3,000 sheets, different combinations possible
	Paper capacity, max	7,150 sheets	7,650 sheets	7,650 sheets	7,650 sheets
	Paper format	A6R-SRA3/A3+	A6R-SRA3/A3+	A6R-SRA3/A3+	A6R-A3+
	Original feeder	Option: DP-7150, DP-7160 or DP-7170	Option: DP-7150, DP-7160 or DP-7170	Option: DP-7150, DP-7160 or DP-7170	Standard (dual scan with multi-feed detection)
	Duplex	Standard	Standard	Standard	Standard
	System memory	4 GB RAM, 64 GB SSD/320 GB HDD or 1 TB	4 GB RAM, 64 GB SSD/320 GB HDD or 1 TB	4 GB RAM, 64 GB SSD/320 GB HDD or 1 TB	4.5 GB RAM, 8 GB SSD/320 GB HDD
Zoom	25%-400%	25%-400%	25%-400%	25%-400%	
Cabinet	Option: no. 81	Option: no. 81	Option: no. 81	--	
<b>Print</b>	Type	Integrated within the system	Integrated within the system	Integrated within the system	Integrated within the system
	Interfaces	USB 3.0, USB 2.0, 10/100/1000BaseTX, USB host, NFC	USB 3.0, USB 2.0, 10/100/1000BaseTX, USB host, NFC	USB 3.0, USB 2.0, 10/100/1000BaseTX, USB host, NFC	USB 2.0, 10/100/1000BaseTX, USB host, NFC
	Operating systems	Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016/2019, Novell NetWare, Linux, Mac ex OS 10.9	Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016/2019, Novell NetWare, Linux, Mac ex OS 10.9	Windows 7/8/8.1/10, Server 2008 R2/2012 R2/2016/2019, Novell NetWare, Linux, Mac ex OS 10.9	Windows 7/8/8.1/10, Server 2008 R2/2012 R2/2016/2019, Novell NetWare, Linux, Mac ex OS 10.9
Emulations	PCL6 (5e, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIe, PDF 2.0, XPS	PCL6 (5e, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIe, PDF 2.0, XPS	PCL6 (5e, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIe, PDF 2.0, XPS	PCL6 (5e, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIe, XPS	
<b>Network</b>	Interfaces	10/100/1000BaseTX	10/100/1000BaseTX	10/100/1000BaseTX	10/100/1000BaseTX
	Network protocols	TCP/IP, Net BEUI	TCP/IP, Net BEUI	TCP/IP, Net BEUI	TCP/IP, Net BEUI
	Operating systems	Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016/2019	Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016/2019	Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016/2019	Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016/2019
<b>Scan</b>	Scan type	CCD colour and b/w	CCD colour and b/w	CCD colour and b/w	CCD colour and b/w
	Scan resolution	200, 300, 400, 600 dpi	200, 300, 400, 600 dpi	200, 300, 400, 600 dpi	200, 300, 400, 600 dpi
	Interfaces	10/100/1000BaseTX	10/100/1000BaseTX	10/100/1000BaseTX	10/100/1000BaseTX
	Network protocols	TCP/IP	TCP/IP	TCP/IP	TCP/IP
<b>Fax</b>	Originals	max A3	max A3	max A3	max A3
	Modem speed	33.6 kbps	33.6 kbps	33.6 kbps	33.6 kbps
	Compression method	JBIG, MMR, MR, MH	JBIG, MMR, MR, MH	JBIG, MMR, MR, MH	JBIG, MMR, MR, MH
	One-touch dial/abbr. dial	1,000/2,000	1,000/2,000	1,000/2,000	1,000/2,000

# A4 MULTIFUNCTIONAL SYSTEMS



		P-3521 MFP	P-3527w MFP
<b>Copy</b>	Copy speed	35 A4 pages/min	35 A4 pages/min
	Copy resolution	600 x 600 dpi	600 x 600 dpi
	Greyscale	256	256
	Standard paper feed	350 (1 x 250 + 100 sheets)	350 (1 x 250 + 100 sheets)
	Optional paper feed	2 x 250 sheets	2 x 250 sheets
	Paper capacity, max	850 sheets	850 sheets
	Paper format	A6R-A4	A6R-A4
	Original feeder	Standard	Standard
	Duplex	Standard	Standard
	System memory	512 MB RAM (max 1,536 MB RAM)	512 MB RAM (max 1,536 MB RAM)
Zoom	25%–400%	25%–400%	
Cabinet	Option: no. 78	Option: no. 78	
<b>Print</b>	Type	Integrated within the system	Integrated within the system
	Interfaces	10/100/1000BaseTX, USB 2.0, USB host, SD slot	10/100/1000BaseTX, USB 2.0, USB host, SD slot, Wi-Fi
	Operating systems	Windows XP, Vista, Windows 7/8/8.1/10, Server 2003/2008 R2/2012 R2/2016/2019, Linux, Mac ex OS 10.6	Windows XP, Vista, Windows 7/8/8.1/10, Server 2003/2008 R2/2012 R2/2016/2019, Linux, Mac ex OS 10.6
Emulations	PCL6 (5e, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIe, Line Printer, IBM Proprinter, Epson LQ-850, PDF 1.7, XPS, Open XPS	PCL6 (5e, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIe, Line Printer, IBM Proprinter, Epson LQ-850, PDF 1.7, XPS, Open XPS	
<b>Network</b>	Interfaces	10/100/1000BaseTX	10/100/1000BaseTX
	Network protocols	TCP/IP, Net BEUI	TCP/IP, Net BEUI
	Operating systems	Windows XP, Vista, Windows 7/8/8.1/10, Server 2003/2008 R2/2012 R2	Windows XP, Vista, Windows 7/8/8.1/10, Server 2003/2008 R2/2012 R2
<b>Scan</b>	Scan type	CIS colour and b/w	CIS colour and b/w
	Scan resolution	200, 300, 400, 600 dpi	200, 300, 400, 600 dpi
	Interfaces	10/100/1000BaseTX, USB 2.0	10/100/1000BaseTX, USB 2.0
	Network protocols	TCP/IP	TCP/IP
<b>Fax</b>	Originals	--	max A4
	Modem speed	--	33.6 kbps
	Compression method	--	JBIG, MMR, MR, MH
	One-touch dial/abbr. dial	--	100/200

# A4 MULTIFUNCTIONAL SYSTEMS



**P-4020 MFP**

<b>Copy</b>	Copy speed	40 A4 pages/min
	Copy resolution	600 x 600 dpi
	Greyscale	256
	Standard paper feed	350 (1 x 250 + 100 sheets)
	Optional paper feed	2 x 250 sheets
	Paper capacity, max	850 sheets
	Paper format	A6R-A4
	Original feeder	Standard (Duplex Scan)
	Duplex	Standard
	System memory	512 MB RAM (max 1,536 MB RAM)
Zoom	25%–400%	
Cabinet	Option: no. 78	
<b>Print</b>	Type	Integrated within the system
	Interfaces	10/100/1000BaseTX, USB 2.0, USB host, SD slot
	Operating systems	Windows XP, Vista, Windows 7/8/8.1/10, Server 2003/2008 R2/2012 R2/2016/2019, Linux, Mac ex OS 10.6
Emulations		PCL6 (5e, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIe, Line Printer, IBM Proprinter, Epson LQ-850, PDF 1.7, XPS, Open XPS
<b>Network</b>	Interfaces	10/100/1000BaseTX
	Network protocols	TCP/IP, Net BEUI
	Operating systems	Windows XP, Vista, Windows 7/8/8.1/10, Server 2003/2008 R2/2012 R2
<b>Scan</b>	Scan type	CIS colour and b/w
	Scan resolution	200, 300, 400, 600 dpi
	Interfaces	10/100/1000BaseTX, USB 2.0
	Network protocols	TCP/IP
<b>Fax</b>	Originals	--
	Modem speed	--
	Compression method	--
	One-touch dial/abbr. dial	--

**P-4025w MFP**

Copy speed	40 A4 pages/min
Copy resolution	600 x 600 dpi
Greyscale	256
Standard paper feed	350 (1 x 250 + 100 sheets)
Optional paper feed	2 x 250 sheets
Paper capacity, max	850 sheets
Paper format	A6R-A4
Original feeder	Standard (Duplex Scan)
Duplex	Standard
System memory	512 MB RAM (max 1,536 MB RAM)
Zoom	25%–400%
Cabinet	Option: no. 78
Type	Integrated within the system
Interfaces	10/100/1000BaseTX, USB 2.0, USB host, SD slot, Wi-Fi
Operating systems	Windows XP, Vista, Windows 7/8/8.1/10, Server 2003/2008 R2/2012 R2/2016/2019, Linux, Mac ex OS 10.6
Emulations	PCL6 (5e, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIe, Line Printer, IBM Proprinter, Epson LQ-850, PDF 1.7, XPS, Open XPS
Interfaces	10/100/1000BaseTX
Network protocols	TCP/IP, Net BEUI
Operating systems	Windows XP, Vista, Windows 7/8/8.1/10, Server 2003/2008 R2/2012 R2
Scan type	CIS colour and b/w
Scan resolution	200, 300, 400, 600 dpi
Interfaces	10/100/1000BaseTX, USB 2.0
Network protocols	TCP/IP
Originals	max A4
Modem speed	33.6 kbps
Compression method	JBIG, MMR, MR, MH
One-touch dial/abbr. dial	100/200



**P-4026iw MFP**

Copy speed	40 A4 pages/min
Copy resolution	600 x 600 dpi
Greyscale	256
Standard paper feed	350 (1 x 250 + 100 sheets)
Optional paper feed	2 x 250 sheets
Paper capacity, max	850 sheets
Paper format	A6R-A4
Original feeder	Standard (Duplex Scan)
Duplex	Standard
System memory	512 MB RAM (max 1,536 MB RAM)
Zoom	25%–400%
Cabinet	Option: no. 78
Type	Integrated within the system
Interfaces	10/100/1000BaseTX, USB 2.0, USB host, SD slot, Wi-Fi
Operating systems	Windows XP, Vista, Windows 7/8/8.1/10, Server 2003/2008 R2/2012 R2/2016/2019, Linux, Mac ex OS 10.6
Emulations	PCL6 (5e, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIe, Line Printer, IBM Proprinter, Epson LQ-850, PDF 1.7, XPS, Open XPS
Interfaces	10/100/1000BaseTX
Network protocols	TCP/IP, Net BEUI
Operating systems	Windows XP, Vista, Windows 7/8/8.1/10, Server 2003/2008 R2/2012 R2
Scan type	CIS colour and b/w
Scan resolution	200, 300, 400, 600 dpi
Interfaces	10/100/1000BaseTX, USB 2.0
Network protocols	TCP/IP
Originals	max A4
Modem speed	33.6 kbps
Compression method	JBIG, MMR, MR, MH
One-touch dial/abbr. dial	100/200

# A4 MULTIFUNCTIONAL SYSTEMS



		P-4531 MFP	P-4536 MFP	P-4531i MFP	P-4536i MFP
<b>Copy</b>	Copy speed	45 A4 pages/min	45 A4 pages/min	45 A4 pages/min	45 A4 pages/min
	Copy resolution	600 x 600 dpi	600 x 600 dpi	600 x 600 dpi	600 x 600 dpi
	Greyscales	256	256	256	256
	Standard paper feed	600 (1 x 500 + 100 sheets)	600 (1 x 500 + 100 sheets)	600 (1 x 500 + 100 sheets)	600 (1 x 500 + 100 sheets)
	Optional paper feed	4 x 500 sheets	4 x 500 sheets	4 x 500 sheets	4 x 500 sheets
	Paper capacity, max	2,600 sheets	2,600 sheets	2,600 sheets	2,600 sheets
	Paper format	A6R-A4	A6R-A4	A6R-A4	A6R-A4
	Original feeder	Standard	Standard	Standard	Standard
	Duplex	Standard	Standard	Standard	Standard
	System memory	1 GB RAM, (max 3 GB RAM), 32/64/128/256/512 GB SSD	1 GB RAM, (max 3 GB RAM), 32/64/128/256/512 GB SSD	1 GB RAM, (max 3 GB RAM), 32/64/128/256/512 GB SSD	1 GB RAM, (max 3 GB RAM), 32/64/128/256/512 GB SSD
Zoom	25%–400%	25%–400%	25%–400%	25%–400%	
Cabinet	Option: high no. 79, low no. 80	Option: high no. 79, low no. 80	Option: high no. 79, low no. 80	Option: high no. 79, low no. 80	
<b>Print</b>	Type	Integrated within the system	Integrated within the system	Integrated within the system	Integrated within the system
	Interfaces	USB 2.0, 10/100/1000BaseTX, USB host	USB 2.0, 10/100/1000BaseTX, USB host	USB 2.0, 10/100/1000BaseTX, USB host	USB 2.0, 10/100/1000BaseTX, USB host
	Operating systems	Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016/2019, Novell NetWare, Linux, Mac ex OS 10.5	Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016/2019, Novell NetWare, Linux, Mac ex OS 10.5	Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016/2019, Novell NetWare, Linux, Mac ex OS 10.5	Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016/2019, Novell NetWare, Linux, Mac ex OS 10.5
Emulations	PCL6 (5e, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIe, Line Printer, IBM Proprinter X24E, Epson LQ-850, PDF 1.7, XPS	PCL6 (5e, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIe, Line Printer, IBM Proprinter X24E, Epson LQ-850, PDF 1.7, XPS	PCL6 (5e, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIe, Line Printer, IBM Proprinter X24E, Epson LQ-850, PDF 1.7, XPS	PCL6 (5e, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIe, Line Printer, IBM Proprinter X24E, Epson LQ-850, PDF 1.7, XPS	
<b>Network</b>	Interfaces	10/100/1000BaseTX	10/100/1000BaseTX	10/100/1000BaseTX	10/100/1000BaseTX
	Network protocols	TCP/IP, Net BEUI	TCP/IP, Net BEUI	TCP/IP, Net BEUI	TCP/IP, Net BEUI
	Operating systems	Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016/2019	Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016/2019	Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016/2019	Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016/2019
<b>Scan</b>	Scan type	CCD colour and b/w	CCD colour and b/w	CCD colour and b/w	CCD colour and b/w
	Scan resolution	200, 300, 400, 600 dpi	200, 300, 400, 600 dpi	200, 300, 400, 600 dpi	200, 300, 400, 600 dpi
	Interfaces	10/100/1000BaseTX, USB 2.0	10/100/1000BaseTX, USB 2.0	10/100/1000BaseTX, USB 2.0	10/100/1000BaseTX, USB 2.0
	Network protocols	TCP/IP	TCP/IP	TCP/IP	TCP/IP
<b>Fax</b>	Originals	--	max A4	--	max A4
	Modem speed	--	33.6 kbps	--	33.6 kbps
	Compression method	--	JBIG, MMR, MR, MH	--	JBIG, MMR, MR, MH
	One-touch dial/abbr. dial	--	22/100	--	100/200

# A4 MULTIFUNCTIONAL SYSTEMS



		P-5536i MFP	P-6038i MFP	P-6038if MFP*
<b>Copy</b>	Copy speed	55 A4 pages/min	60 A4 pages/min	60 A4 pages/min
	Copy resolution	600 x 600 dpi	600 x 600 dpi	600 x 600 dpi
	Greyscales	256	256	256
	Standard paper feed	600 (1 x 500 + 100 sheets)	600 (1 x 500 + 100 sheets)	600 (1 x 500 + 100 sheets)
	Optional paper feed	4 x 500 sheets	4 x 500 sheets	4 x 500 sheets
	Paper capacity, max	2,600 sheets	2,600 sheets	2,600 sheets
	Paper format	A6R-A4	A6R-A4	A6R-A4
	Original feeder	Standard (Duplex Scan)	Standard (dual scan with multi-feed detection)	Standard (dual scan with multi-feed detection)
	Duplex	Standard	Standard	Standard
	System memory	1 GB RAM (max 3 GB RAM), 32/64/128/256/512 GB SSD	1 GB RAM (max 3 GB RAM), 32/64/128/256/512 GB SSD	1 GB RAM (max 3 GB RAM), 32/64/128/256/512 GB SSD
Zoom	25%–400%	25%–400%	25%–400%	
Cabinet	Option: high no. 79, low no. 80	Option: high no. 79, low no. 80	Option: high no. 79, low no. 80	
<b>Print</b>	Type	Integrated within the system	Integrated within the system	Integrated within the system
	Interfaces	USB 2.0, 10/100/1000BaseTX, USB host	USB 2.0, 10/100/1000BaseTX, USB host, SD slot	USB 2.0, 10/100/1000BaseTX, USB host, SD slot
	Operating systems	Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016/2019, Novell NetWare, Linux, Mac ex OS 10.5	Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016/2019, Novell NetWare, Linux, Mac ex OS 10.9	Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016/2019, Novell NetWare, Linux, Mac ex OS 10.9
Emulations		PCL6 (5e, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIe, Line Printer, IBM Proprinter X24E, Epson LQ-850, PDF 1.7, XPS	PCL6 (5e, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIe, Line Printer, IBM Proprinter X24E, Epson LQ-850, PDF 1.7, XPS	PCL6 (5e, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIe, Line Printer, IBM Proprinter X24E, Epson LQ-850, PDF 1.7, XPS
<b>Network</b>	Interfaces	10/100/1000BaseTX	10/100/1000BaseTX	10/100/1000BaseTX
	Network protocols	TCP/IP, Net BEUI	TCP/IP, Net BEUI	TCP/IP, Net BEUI
	Operating systems	Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016/2019	Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016/2019	Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016/2019
<b>Scan</b>	Scan type	CCD colour and b/w	CCD colour and b/w	CCD colour and b/w
	Scan resolution	200, 300, 400, 600 dpi	200, 300, 400, 600 dpi	200, 300, 400, 600 dpi
	Interfaces	10/100/1000BaseTX, USB 2.0	10/100/1000BaseTX, USB 2.0	10/100/1000BaseTX, USB 2.0
	Network protocols	TCP/IP	TCP/IP	TCP/IP
<b>Fax</b>	Originals	max A4	max A4	max A4
	Modem speed	33.6 kbps	33.6 kbps	33.6 kbps
	Compression method	JBIG, MMR, MR, MH	JBIG, MMR, MR, MH	JBIG, MMR, MR, MH
	One-touch dial/abbr. dial	100/200	100/200	100/200

\* P-6038if MFP comes standard with a 250 sheet staple finisher and optionally has a 320 GB hard drive and a Trusted Platform module

# A3 PRINT SYSTEMS



## P-6040DN

<b>Print format</b>	A6R-SRA3
<b>Print speed</b>	60 A4 / 30 A3 pages/min
<b>Print resolution</b>	1,200 x 1,200 dpi
<b>Standard paper feed</b>	1,150 (2 x 500 + 150 sheets)
<b>Optional paper feed</b>	2 x 500, 2 x 1,500, 3,000 sheets
<b>Duplex</b>	Standard
<b>Processor</b>	Freescale QoriQ T1024 (Dual Core) 1.2 GHz
<b>Print memory</b>	4 GB RAM, 8 GB SSD, 320 GB HDD
<b>Interfaces</b>	USB 2.0, USB host, 10/100/1000BaseTX, NFC
<b>Interfaces optional</b>	--
<b>Emulations</b>	PCL6 (5e, XL), KPDL 3 (PostScript 3 compatible), PDF 1.7, PRESCRIBE IIe, XPS

# A4 PRINT SYSTEMS



## P-3522DW

<b>Print format</b>	A6R-A4
<b>Print speed</b>	35 A4 pages/min
<b>Print resolution</b>	600 x 600 dpi, 1,200 x 1,200 dpi
<b>Standard paper feed</b>	350 (250 + 100 sheets)
<b>Optional paper feed</b>	2 x 250 sheets
<b>Duplex</b>	Standard
<b>Processor</b>	Cortex-A9 / 800 MHz
<b>Print memory</b>	256 MB (max 256 MB)
<b>Interfaces</b>	10/100/1000BaseTX, USB 2.0, USB host, SD slot, Wi-Fi
<b>Interfaces optional</b>	--
<b>Emulations</b>	PCL6 (5e, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIe, Line Printer, IBM Proprinter, Epson LQ-850, PDF 1.7, XPS, Open XPS



## P-4020DN

<b>Print format</b>	A6R-A4
<b>Print speed</b>	40 A4 pages/min
<b>Print resolution</b>	600 x 600 dpi, 1,200 x 1,200 dpi
<b>Standard paper feed</b>	350 (250 + 100 sheets)
<b>Optional paper feed</b>	2 x 250 sheets
<b>Duplex</b>	Standard
<b>Processor</b>	Cortex-A9 / 800 MHz
<b>Print memory</b>	256 MB (max 256 MB)
<b>Interfaces</b>	10/100/1000BaseTX, USB 2.0, USB host, SD slot
<b>Interfaces optional</b>	--
<b>Emulations</b>	PCL6 (5e, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIe, Line Printer, IBM Proprinter, Epson LQ-850, PDF 1.7, XPS, Open XPS

## P-4020DW

<b>Print format</b>	A6R-A4
<b>Print speed</b>	40 A4 pages/min
<b>Print resolution</b>	600 x 600 dpi, 1,200 x 1,200 dpi
<b>Standard paper feed</b>	350 (250 + 100 sheets)
<b>Optional paper feed</b>	2 x 250 sheets
<b>Duplex</b>	Standard
<b>Processor</b>	Cortex-A9 / 800 MHz
<b>Print memory</b>	256 MB (max 256 MB)
<b>Interfaces</b>	10/100/1000BaseTX, USB 2.0, USB host, SD slot, Wi-Fi
<b>Interfaces optional</b>	--
<b>Emulations</b>	PCL6 (5e, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIe, Line Printer, IBM Proprinter, Epson LQ-850, PDF 1.7, XPS, Open XPS



## P-4532DN

<b>Print format</b>	A6R-A4
<b>Print speed</b>	45 A4 pages/min
<b>Print resolution</b>	1,200 x 1,200 dpi
<b>Standard paper feed</b>	600 (500 + 100 sheets)
<b>Optional paper feed</b>	4 x 500 sheets
<b>Duplex</b>	Standard
<b>Processor</b>	Cortex-A9 / 1.2 GHz
<b>Print memory</b>	512 MB (max 2.5 GB)
<b>Interfaces</b>	10/100/1000BaseTX, USB 2.0, USB host (2), SD slot
<b>Interfaces optional</b>	IEEE 1284 parallel, 10/100/1000BaseTX, WLAN card
<b>Emulations</b>	PCL6 (5e, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIe, Line Printer, IBM Proprinter, XPS, Open XPS



## P-5032DN

<b>Print format</b>	A6R-A4
<b>Print speed</b>	50 A4 pages/min
<b>Print resolution</b>	1,200 x 1,200 dpi
<b>Standard paper feed</b>	600 (500 + 100 sheets)
<b>Optional paper feed</b>	4 x 500 sheets
<b>Duplex</b>	Standard
<b>Processor</b>	Cortex-A9 / 1.2 GHz
<b>Print memory</b>	512 MB (max 2.5 GB)
<b>Interfaces</b>	10/100/1000BaseTX, USB 2.0, USB host (2), SD slot
<b>Interfaces optional</b>	IEEE 1284 parallel, 10/100/1000BaseTX, WLAN card
<b>Emulations</b>	PCL6 (5e, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIe, Line Printer, IBM Proprinter, XPS, Open XPS

## P-5532DN

<b>Print format</b>	A6R-A4
<b>Print speed</b>	55 A4 pages/min
<b>Print resolution</b>	1,200 x 1,200 dpi
<b>Standard paper feed</b>	600 (500 + 100 sheets)
<b>Optional paper feed</b>	4 x 500 sheets
<b>Duplex</b>	Standard
<b>Processor</b>	Cortex-A9 / 1.2 GHz
<b>Print memory</b>	512 MB (max 2.5 GB)
<b>Interfaces</b>	10/100/1000BaseTX, USB 2.0, USB host (2), SD slot
<b>Interfaces optional</b>	IEEE 1284 parallel, 10/100/1000BaseTX, WLAN card
<b>Emulations</b>	PCL6 (5e, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIe, Line Printer, IBM Proprinter, XPS, Open XPS

## P-6033DN

<b>Print format</b>	A6R-A4
<b>Print speed</b>	60 A4 pages/min
<b>Print resolution</b>	1,200 x 1,200 dpi
<b>Standard paper feed</b>	600 (500 + 100 sheets)
<b>Optional paper feed</b>	4 x 500 sheets
<b>Duplex</b>	Standard
<b>Processor</b>	Cortex-A9 / 1.2 GHz
<b>Print memory</b>	512 MB (max 2.5 GB)
<b>Interfaces</b>	10/100/1000BaseTX, USB 2.0, USB host (2), SD slot
<b>Interfaces optional</b>	IEEE 1284 parallel, 10/100/1000BaseTX, WLAN card
<b>Emulations</b>	PCL6 (5e, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIe, Line Printer, IBM Proprinter, XPS, Open XPS



[www.triumph-adler.com](http://www.triumph-adler.com)

We develop **individual processes in the fields of document solutions, information and IT**. Document technology is our core business and we continuously develop our portfolio. At the same time, we assist our customers in creating flexible and modern workplaces with our pioneering mobile solutions and cloud services. Efficient processes are crucial for the success of a company. **We can assist you with solutions for saving time and money with your workflows** and support you with our expertise in implementing professional hardware and software solutions.

TA Triumph-Adler